



Note:
Conduit, drain tubes and cap
may be galvanized steel or PVC.

SECTION B-B
Scale: 3/4"=1'-0"

Note:
All #7 and #8 bars shall be placed
continuously in the parapet from
expansion opening to expansion opening
in a simple span bridge and expansion
opening to centerline of pier in a
multispan bridge. Refer to
BR-SS(6.25)-03-159B.

Note C:
The constr. jt. between the F-shape
parapet and the deck may vary
slightly from the joint indicated.
For exact details and location of the
joint see "Superstructure"
Sheet.

42'' DIAMOND BACK

APPROVAL	
<i>L.S. Friedman</i> DIRECTOR OFFICE OF BRIDGE DEVEL.	
DATE: 6/1/05	
REVISIONS	
SHA	FHWA
FHWA APPROVAL	
DATE: .	

STATE OF MARYLAND
DEPARTMENT OF TRANSPORTATION
STATE HIGHWAY ADMINISTRATION
OFFICE OF BRIDGE DEVELOPMENT

SUPPORT BRACKET FOR BRIDGE MOUNTED LIGHT POST
WITH SINGLE CONDUIT AND 42'' F-SHAPE PARAPET
WITH DIAMOND BACK

STANDARD NO. BR-SS(6.28)-05-167B

SHEET 2 OF 2

SUPER-CONCRETE WORK